

13-IN-1 5 Gbps USB-C

Dual 2K Docking Station

(48 W PSU)

Model: CS500



HIGHLIGHT

- Dual 2K video output with dual HDMI 1.4 ports and dual DP 1.2a ports
- Speedy data speed with 5 Gbps bandwidth delivers responsive file transfer and display
- Six USB ports, a Gigabit ethernet, and an Audio combo port maximize the expansion efficiency
- Compatible with systems with a USB-C 3.2 Gen 1x1 / USB4 / Thunderbolt 3/4 port

INTERFACES

| Upstream USB | USB-C 3.2 Gen 2 Ports (5 Gbps) |
|---------------|---|
| USB | 2× USB-C 3.2 Gen 2 Ports (5 Gbps, Total 14W Max) |
| | 4× USB-A 3.2 Gen 2 Ports (5 Gbps, Total 10W Max) |
| Video Output | 2× DisplayPort 1.2a |
| | 2× HDMI 1.4 |
| | Supporting resolution up to 2× 2K (2560×1600) 60 Hz |
| Network | 1× Gigabit RJ45 Port |
| Audio and Mic | 1× 3.5 mm Combo Jack |
| Buttons | Power On/Off |
| | |

HARDWARE

| Chipset | DisplayLink 6350-N |
|--------------|--|
| Power Supply | External Power Adapter Input: 100 ~ 240 V, 50/60 Hz Output: 12 V = 4 A |
| | Max Power Consumption: 48W |
| | Idle Power Consumption: 5W |

Email: sales@cudy.com

PHYSICAL

| Casing | Silver Gray Color, Matte Finish |
|-----------------|--|
| | Made from a Single Block of Aluminum (CNC Machining) |
| | Anti-Scratch Design (Al6061 T5 Base Material, Sandblasting, and Anodization) |
| Security | 1× Kensington Security Slot |
| Dimension (WDH) | 210×85×19.7 mm (8.27×3.35×0.78 inches) |
| Weight | ~ 350 g |
| Package Content | Docking Station Power Adapter USB-C to USB-C Cable Quick Installation Guide |

REQUIREMENTS

| Hardware | Requires a USB-C 3.2 Gen 1x1 / USB4 / Thunderbolt 3/4 Port |
|---------------|--|
| Compatible OS | Windows 7 or later |
| | macOS 10.14 or later |
| | Ubuntu LTS 18.04 or later |
| | ChromeOS build RS1 or later |
| | Android 5 or higher (Max 1× 1080P. Ethernet Disabled) |
| | Auto driver installation for Windows 10/11 and ChromeOS R51+. Manual driver installation is required for macOS, Windows 7/8/8.1, and Ubuntu. DisplayLink Presenter app is required on Android. |
| Environment | Operating Temperature: -20–60 °C (-10–140 °F) |
| | Storage Temperature: -40–70 °C (-40–158 °F) |
| | Operating Humidity: 10–90% RH non-condensing |
| | Storage Humidity: 5–90% RH non-condensing |

SERVICES

| Warranty | Limited warranty for 2 years |
|----------|------------------------------|
|----------|------------------------------|

Email: sales@cudy.com