




cudy

Model: **RE3600**

BE3600


Mesh Wi-Fi 7 Range Extender

-  Powerful Broadcom 2 GHz Quad-Core CPU
-  Compatible with Any Wi-Fi Router or Gateway
-  3-In-1 Wi-Fi Extender/ Access Point/ Add-on Mesh



Wi-Fi 7

WHOLE HOME
MESH
Expandable Seamless
Coverage



Features

Multi-Link Operation (MLO)

- MLO in Wi-Fi 7 aggregates traffic across multiple bands

Wall-Plug Design

- Easy to install and move

External Antennas

- Provides powerful connectivity and expansive Wi-Fi coverage

Easy Setup

- Setup with the WPS button of the existing router and Cudy RE3600

Ethernet Port

- Connect a wired device for better performance

Enjoy Cudy Whole Home Mesh Wi-Fi System






Extend Your Wireless Coverage with Wi-Fi 7

Say goodbye to Wi-Fi dead zones

A single router has limited Wi-Fi coverage and always causes Wi-Fi dead zones. RE3600 wirelessly connects to your existing router and boosts Wi-Fi signals throughout your home, giving you a smooth Wi-Fi network experience with great capacity and coverage.

More Connections, Better Performance

The latest Wi-Fi 7 technology is built for today's devices, eliminating lag, endless loading and dead spots. It's perfectly suited to your network needs especially for bandwidth-intensive tasks like cloud gaming or 4K UHD video.




- 2882 Mbps on 5 GHz
- 688 Mbps on 2.4 GHz
- Ethernet Cable
- Existing Router Coverage
- Expanded Extender Coverage

Wi-Fi Extender Mode



Access Point Mode





Hardware Specs

Model Version	RE3600 1.0	
CPU	Chipset	BCM6764
	CPU Details	2.0 GHz Quad-Core, ARM Cortex-A7
Memory/Storage	Flash/ROM	128 MB (1 Gbit) NAND
	DDR/RAM	256 MB (2 Gbit) DDR3
Wireless	5 GHz Wi-Fi Speed	2882 Mbps
	2.4 GHz Wi-Fi Speed	688 Mbps
	5 GHz Wi-Fi Streams	2T2R (2×2 MIMO)
	2.4 GHz Wi-Fi Streams	2T2R (2×2 MIMO)
	Wi-Fi Antennas	2× Fixed
	FEM or PA/LNA	• 5 GHz: 2× Internal • 2.4 GHz: 2× Internal
	Range Performance	Max: 150 m (492 ft) Indoor WiFi range varies depending on the layout and wall materials. See Wall Performance spec for placement suggestions.
	Wall Performance	One wooden wall with thickness < 20 cm (7") One concrete wall with thickness < 10 cm (4")
Interfaces	Gigabit RJ45 Ports	1
	LED	• Signal Strength • WPS • Power
	Physical Buttons	• WPS Button • Reset Button

	Power Input	AC Plug
	Power Input Note	EU, US, UK, AU Plug are Available
Power	Power Methods	AC
	AC	100V ~ 240V
Reliability	Environment	Operating Temperature: 0°C ~ 50°C (32°F ~ 122°F) Storage Temperature: -40°C ~ 70°C (-40°F ~ 158°F) Operating Humidity: 10% ~ 90% non-condensing Storage Humidity: 5% ~ 90% non-condensing
	Grounding Methods	Three-Prong Plug
	Certifications	FCC, CE
Mechanical	Install in a Daisy Chain	Recommend to install less than 3 repeaters in a wireless chain.
	Installation	Plug-In-Socket
	Casing Material	Plastic
	Dimension	129.6×80×48.6 mm 5.1×3.15×1.91 inches
Ordering	Retail Package	161×120×96 mm
Information	Dimension	6.34×4.72×3.78 inches
	Units per Carton	30
	Carton Dimension	50.4×37.7×34.1 cm 19.84×14.84×13.43 inches



Software Specs

Model Version	RE3600 1.0	
Wireless	Wi-Fi Standards	Wi-Fi 7
	Max Wi-Fi Modulation	4K-QAM
	Wi-Fi Efficiency	<ul style="list-style-type: none"> • MLO • MRU • Puncturing • OFDMA • MU-MIMO • BSS Color
	Max Capacity	512
	Recommended Client Upper Limit	50
	Max Wi-Fi Channel Width	160 MHz
	WPS	True
	General	Operation Modes
Mesh		Cudy Mesh Satellite
Mesh Backhaul		<ul style="list-style-type: none"> • Wireless Backhaul • Wired Backhaul
Multi-Band Backhaul		true
System	LED Control	ture
	Local Control Method	<ul style="list-style-type: none"> • Config Web Page • App Control
	Remote Control Method	App Control

	Firmware Upgrade	<ul style="list-style-type: none"> • Local Update • App (Over the Air) • Online Update
	Reliability	<ul style="list-style-type: none"> • Timed Reboot • Backup and Restore
Dashboard	Panel	<ul style="list-style-type: none"> • Connected Devices • Host Network Status • Wi-Fi Status • LAN Status • System Version
System	Diagnostic Tools	<ul style="list-style-type: none"> • Ping • Traceroute • NSLookup • System Log
	Languages	<ul style="list-style-type: none"> • English • Bengali • Catalan • Czech • German • Greek • Spanish • French • Hebrew • Croatian • Hungarian • Italian • Japanese • Khmer • Korean • Dutch • Norwegian • Polish • Portuguese • Romanian • Russian • Slovak • Swedish • Thai • Turkish • Ukrainian • Vietnamese • Simplified Chinese • Traditional Chinese
Dashboard	Charts	Mesh Topology
General	Internet Failover	<ul style="list-style-type: none"> • Wired
	Sequence	<ul style="list-style-type: none"> • Wireless