



Model

GS 2024S2

24-Port Gigabit Managed Switch
with 4 SFP Slots



1. Product Overview

28-Port Managed Gigabit Ethernet Switch, black iron shell design, built-in DC 12V Power supply, light and simple, with LED indicator on the panel, can dynamically display the connection and operation of equipment, provide simple fault detection methods, and facilitate maintenance and management; this series of switches provide advanced network management functions: redundant ring network, VLAN, cluster, QoS, speed control, port image, fault alarm and firmware online upgrade. The adaptive port can automatically adapt to the 10m, 100m and 1000m networks, and can automatically adapt to the full duplex or half duplex mode; the MAC address self-learning function ensures error free data transmission; the store and forward mode prevents the damaged packets from flooding in the network; the flow control function can prevent the impact of a large amount of instantaneous data on the network; the port supports MDI/ Mdx auto flip function, non-blocking line speed transmission of all ports.

It is mainly located in the core or convergence layer of user networks such as industrial parks, buildings, factories and mines, government agencies, community broadband, etc.; it can be widely used in Ethernet access scenarios such as small and medium-sized enterprises, Internet cafes, hotels, schools, etc.

2. Product Features

1. Support 24* Gigabit Ethernet Ports+ 4* Gigabit SFP Ports+1* Console Port
2. Support IEEE802.3, IEEE802.3i, IEEE802.3u, IEEE802.3ab, IEEE802.3z, Storage and forwarding
3. Ethernet ports support 10/100/1000M adaptive
4. Adopt store-and-forward switching mechanism
5. Adopt store-and-forward switching mechanism
6. Fanless design, natural Cooling, 1U Rack Mount
7. Support 802.1x port authentication, support AAA authentication, support TACACS+ authentication
8. Support WEB, TELNET, CLI, SSH, SNMP, RMON management

3. Specification

Model	GS2024S2
Power	AC INPUT (100-240V)
Ethernet	24* Gigabit Ethernet Ports 4* Gigabit SFP Ports 1* Console Port
Bandwidth	56Gbps
Packet Forwarding Rate	41.66Mpps
Package Cache	4Mb
Memory	128M
Flash Memory	16M
MAC Address	8K
VLANs	4096
Jumbo Frame	9.6Kbytes
Transfer Mode	Storage & Forwarding
MTBF	100000 Hours

Standard	
Network Protocol	IEEE802.3 (Ethernet)
	IEEE802.3u (Rapid Ethernet)
	IEEE 802.3ab (Gigabit Ethernet)
	IEEE 802.3z (Gigabit Ethernet Optic Fiber)
	IEEE802.3x (Flow Control)
	IEEE 802.3az (Energy-efficient Ethernet)
	IEEE 802.3ad (Link aggregation)
	IEEE 802.1AB LLDP/LLDP-MED (Link Layer Discovery Protocol)
	IEEE 802.1D Spanning Tree Protocol STP
	IEEE 802.1w Rapid Spanning Tree Protocol RSTP
	IEEE 802.1s Multiple Spanning Tree Protocol MSTP
	IEEE 802.1Q (Virtual LAN)
	IEEE 802.1p (VLAN Label)
IEEE 802.1X (User authentication)	
Optical Medium	Multi-mode fiber: 50/125, 62.5/125, 100/140um
	Single mode fiber: 8/125, 8.7/125, 9/125, 10/125um
Network Medium	10Base-T: Cat 3, 4, 5 or above UTP(≤100m)
	100Base-TX: Cat 5 or above UTP(≤100m)
	1000Base-TX: Cat 5 or above UTP(≤100m)
Industry Standard	EMI: FCC Part 15 CISPR (EN55032) class A
	EMS: EN61000-4-2 (ESD),
	EN61000-4-4 (EFT), EN61000-4-5 (Surge)

Environment Standard	
Working Environment	Working Temperature: -10~50°C
	Storage Temperature: -40~70°C
	Working Humidity: 10%~90%, non-condensing
	Storage Temperature: 5%~90%, non-condensing
Function Indicator	
Indicator	PWR(Power Indicator);
	SYS(System Light);
	Link/Act(Link & Data)
PWR	On: Powered On
	Off: Powered Off
SYS	Off: System Off
	On: System On
Link/ACT	On: No Data
	Flashing: Data Transmit
	Off: Link Connection Blocked

Physical Specification

Structure Size	Product Size: 440*204*44mm
	Package Size: 500*290*85mm
	Product N. W: 2.45kg
	Product G. W: 3.06kg
Packing Info	MEAS: 520*445*310MM
	Packing Qty: 5PCS
	Packing Weight: 16.3 KG
Power Voltage	Machine Input Voltage: AC 100-240V; Built-in power output: DC12V3A; Total Power: 36W
Package List	Switch: 1PCS; Power cable: 1PCS; Serial cable: 1PCS; Instruction manual: 1PCS; Certificate of quality: 1PCS; Warranty card: 1PCS; Mounting ear: 1 Pair

Layer 2 Software Function

Port Management	Enable/Disable Port Speed, Duplex, MTU Setting Flow-control Port Information Check
Port Mirroring	Supports both side-way port mirroring
Port Speed Limit	Support port rate limiting, the granularity of rate limiting is 32Kbps
Port Isolation	Support port isolation Settings
Storm Suppression	Supports unknown unicast, unknown multicast, and broadcast storm suppression
Link Aggregation	Support static manual aggregation Support LACP dynamic aggregation Access
VLAN	Trunk hybrid Support VLAN division based on port, protocol, and MAC address, VLAN tunnel Support GVRP dynamic VLAN registration Voice VLAN
MAC	Support static addition, deletion MAC address learning limit Support dynamic aging time setting
Spanning Tree	802.1D Spanning Tree Protocol (STP) 802.1w Rapid Spanning Tree Protocol(RSTP) 802.1s Multi Spanning Tree Protocol(MSTP)
Multicast	Support static addition, deletion, IGMP-snooping Support MLD-Snooping Support v1/2/3 dynamic multicast monitor
DDM	Support SFP/SFP+DDM

Layer 3 Function	
Routing Function	Static routing
IP	IPV4, IPV6 Interface
ARP	Support ARP
Extended Function	
ACL	Based on source MAC, destination MAC, protocol type, source IP, destination IP, L4 port
QOS	Based on 802.1p (COS) classification Based on DSCP classification Classification based on source IP, destination IP, and port number Support SP, WRR scheduling strategy Support flow rate limit CAR
LLDP	Support LLDP link discovery protocol
User Setting	Add/delete users
Log	User login, operation, status, events
Anti-attack	DOS Defense Support CPU protection and limits the rate of sending CPU packets ARP binding (IP, MAC, PORT binding)
Certification	Support 802.1x port authentication Support AAA certification
Network diagnosis	Support ping, telnet, trace
System Management	Device reset, configuration save/restore, upgrade management, time setting, etc

Management Function	
CLI	Support serial port command line management
SSH	Support SSHv1/2 remote management
TELNET	Support telnet remote management
WEB	Support Layer 2 settings, Layer 2 and Layer 3 monitor
SNMP	SNMP V1/V2/V3 Support trap: ColdStart, WarmStart, LinkDown, LinkUp
RMON	Support RMON v1
Other Functions	Support DHCP Snooping, Option82, DHCP Server Support dynamic ARP detection Support TACACS+ certification Support DNS Setting Support port security setting Support MVR protocol Support cable detection VCT function Support UDLD protocol