



Model: UH500

4K 30Hz

5 Gbps USB-C Hub

4K 30 Hz
HDMI 1.4

5 Gbps
Transmission

Max 100W
PD Input



[Datasheet](#)

Highlights

Plug-and-Play USB-C dongle for extending one USB-C to HDMI and four USB-A ports, ideal for business people, lecturers, and school students.

- 4K 30Hz Output via HDMI 1.4
- 100W Passthrough PD
- 4× 5 Gbps USB-A 3.2 Gen 1
- 48 g (1.69 oz.)
- 113.1×44.2×15.7 mm (4.45×1.74×0.62")
- Works with PC/Mac/iPad/iPhone/Android/Nintendo

Hardware Features

Interfaces	Upstream Port	1× USB-C 3.2 Gen 1 Port (5 Gbps)
	Video Output	1× HDMI 1.4
	Video Output Note	4K (4096×2160) 30 Hz
		2K (2560×1440) 60 Hz
		1080P (1920×1080) 120 Hz
	USB Ports	4× USB-A 3.2 Gen 1 Ports (5 Gbps)
	Power Input	USB-C Port
Physical Buttons	NA	

Power	Power Methods	DC / PD
	DC	5~20V 0~5A
	Max Power Consumption (W)	100W if powered by a PD Adapter
		10W if powered by the host client's USB Power
Idle Power Consumption (W)	2W	
Physical	Color	Silver Gray Color
	Casing	Aluminum
		ABS
		PC
Requirements	Hardware Requirement	Requires a USB-C 3.2 Gen 1 / USB4 / Thunderbolt 3/4 port on the client device
		Compatible OS
	macOS 10.12 or later	
	Ubuntu LTS 18.04 or later	
	Android 5 or higher	
	iPadOS	
	iOS	
Driver Installation	Driver Free	
Reliability	Environment	Operating Temperature: 0~40 °C (-32~104 °F)
		Storage Temperature: -20~70 °C (-10~158 °F)
		Operating Humidity: 20~85% RH non-condensing
		Storage Humidity: 10~90% RH non-condensing
Mechanical	Product Weight	48g (1.69 oz.)
	Dimension	113.1×44.2×15.7 mm
		4.45×1.74×0.62 inches
Ordering Informaiton	Retail Package Weight	89g (1.69 oz.)